

**PRV**PATENT- OCH REGISTRERINGSVERKET  
Patentavdelningen

REC'D 16 FEB 2005

WIPO

PCT

**Intyg  
Certificate**

*Härmed intygas att bifogade kopior överensstämmer med de handlingar som ursprungligen ingivits till Patent- och registreringsverket i nedannämnda ansökan.*

*This is to certify that the annexed is a true copy of the documents as originally filed with the Patent- and Registration Office in connection with the following patent application.*

(71) Sökande Gyros AB, Uppsala SE  
Applicant (s)

(21) Patentansökningsnummer 0400181-4  
Patent application number

(86) Ingivningsdatum 2004-01-29  
Date of filing

Stockholm, 2005-02-08

För Patent- och registreringsverket  
For the Patent- and Registration Office

  
Gunilla Larsson

Avgift  
Fee

**PRIORITY  
DOCUMENT**

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

2004-01-29

GY 0068SE

1

2004-0129

Huvudfaxen Kassan

**SEGMENTED POROUS BEDS AND PRELOADED MICROSCALE DEVICES****TECHNICAL FIELD**

The invention relates to a microfluidic device for performing experiments which each  
5 comprises interaction between a solid phase material and a solute that is present in a liquid. The solid phase material is present in the device as porous beds during the experiments. The device permits that one or more experiments can be carried out in parallel.

- 10 In the 1<sup>st</sup>, 2<sup>nd</sup> and 3<sup>rd</sup> aspects an important feature is that the porous bed is in a dry state and comprises a bed-preserving agent. See claims 4-10. In the fourth aspect an important feature is that the porous bed comprises an upstream part and a downstream part where a reactant that is capable of reacting with a solute in a through-passing liquid primarily is immobilized to the solid phase material of the downstream part.
- 15 See claims 1-3.

Parallelity means that at least a sequence containing the binding step is similar for the experiments, i.e. the periods of time during which the solid phase material is in contact with the corresponding solutions and the sequence in which the solutions are  
20 used are essentially the same. The reagents/reactants used may be different.

The term "solute" comprises true solutes, microorganisms including viruses, suspended cells, suspended cell parts and various other reactants that are in dissolved or colloidal form and sufficiently small to be transported by liquid flow through the  
25 bed.

The term "microfluidic device" means that the device comprises one or more microchannel structures in which liquid flow is used for transporting various kinds of reactants, analytes, products, samples, buffers and/or the like. The terms "micro" in  
30 "microchannel structure" contemplates that there are one or more cavities and/or conduits that have a cross-sectional dimension that is  $\leq 10^3 \mu\text{m}$ , preferably  $\leq 5 \times 10^2 \mu\text{m}$ , such as  $\leq 10^2 \mu\text{m}$ . The device is capable of processing liquid aliquots in the nanolitre (nl) range (which includes the picolitre (pl) range). The nl-range has an

GY 0068SE  
2004-0129

2

Huvudtaxen Kassan

upper end of 5,000 nl but relates in most cases to volumes  $\leq 1,000$  nl, such as  $\leq 500$  nl or  $\leq 100$  nl.

The interaction between the solute and the porous bed contemplates e.g.

- 5 a) separation of the solute from the liquid, i.e. the solute is retained by the solid so that bed and the solute can be separated from each other,
- b) interaction as part of a catalytic reaction, e.g. an enzymatic reaction, and/or
- c) solid phase synthesis.

- 10 Patent publications cited herein are incorporated by reference in their entirety.

#### BACKGROUND PUBLICATIONS

- WO 0275312 (Gyros AB) focuses on affinity assays for the characterization of reaction variables by binding a soluble affinity reactant to a solid phase material that
- 15 comprises in immobilized form the counterpart to the affinity reactant. The solid phase is represented by the inner wall of the reaction microcavity or by a porous bed placed in the reaction microcavity.

- SE 0201310 (Gyros AB) describes performing catalytic assays with one part of the
- 20 used catalytic system being immobilized. The assays are illustrated with enzyme systems. The immobilization techniques and support materials are in principle the same as in WO 0275312 (Gyros AB).

- US 5,726,026 (Univ. Pennsylvania) and US 5,928,880 (Univ. Pennsylvania) describe
- 25 in a side sentence a microfluidic device that comprises a detection/reaction zone containing a solid phase material in particle form. Streptavidin is immobilized to the particles. The particles may be dried or lyophilized.

- US 6,479,299 (Caliper) discusses predispensation of soluble and insoluble reagents
- 30 (assay components) during the manufacture of a microfluidic device. Insoluble reagents may be in lyophilized form.

GY 0068SE

3

2004-0129

Applicant has marketed a microscale fluidic device (Gyrolab MALDI SP1) containing a plurality of microchannel structures each of which contains a column of a reverse solid phase material (hydrophobic beads) (WO 02075775 (Gyros AB) and WO 0275776 (Gyros AB)). The solid phase material is in a dry state. In order to secure that the beads are retained in the correct location during storage and transport, the packages of the devices have been specifically designed.

WO 56808 (Gyros AB), WO 0147437 (Gyros AB), WO 0154810 (Gyros AB), WO 02075775 (Gyros AB) and WO 0275776 (Gyros AB) suggest in general terms to deliver microfluidic devices in dry form.

US 5,354,654 (Ligler et al) suggests a kit comprising a solid support with an immobilized ligand-receptor complex that has been lyophilized together with a cryostabilisator. Packing of the support in a macroscale column is suggested.

15

US 5,998,155 (Squibb) and US 5,691,152 (Squibb) describes compositions having a high biotin-binding activity and comprising a biotin-binding moiety immobilized to a polymer support. The support may be in beaded form and lyophilized together with (a) a bulking agent protecting the beads from damages during freeze-drying and assisting the reswelling of the beads, (b) a protectant for inhibiting chemical reactions during freeze-drying and storage, (c) buffers etc.

#### BACKGROUND PROBLEMS

There are a number of technical problems associated with providing the market with microfluidic devices of the type discussed above. We have found that in the case the customer would introduce the hydrophilic porous bed into the device, there will be a high risk for obtaining mal-functioning beds. In total this would lead to increased inter- and intra-device variations in performance of the beds/microchannel structures, decreased sensitivity and reproducibility, etc.

30

In the macroworld the general trend has been to provide preloaded columns with solid phase based separation media in bed form in a wet state and easily controlled. Losses of liquid during storage due to evaporation typically are low compared to the total

GY 0068SE

4

2004-01-29

2004-01-29

volume. The situation is quite different for microfluidic devices where bed volumes typically are in the nl-range. Evaporation is assisted by wicking, easily becomes significant and results in quick uncontrolled drying of a bed and an unacceptable risk for the creation of channels, cavities and inclusion of air that will disturb the liquid flow characteristics of the bed. For solid phase material comprising a bioactive reactant the risk for irreproducible and irreversible changes in activity is also apparent. There are difficulties in reconstituting fully or partly dried solid phase material in microfluidic devices to minute well-ordered and homogeneous porous beds/columns having the liquid flow characteristics and binding activity with essentially the same inter-channel and inter-device variation as the wet beds had before drying.

These problems are typically more pronounced for hydrophilic and/or water-swella-  
ble solid phase material than for hydrophobic that do not swell in water. See figures 2a-b  
and 3.

Our experience with wet hydrophilic beds implanted the idea that the beds have to be  
dried under controlled conditions. It still, however, turned out difficult to implement  
dried solid phase material that could be reconstituted in the desired way to minute  
porous beds/columns, e.g.

- The solid phase material typically carries a reactant that is sensitive to drying, storage and transportation.
- The binding of the solute to a porous bed in a microfluidic device may in many variants of microfluidic devices be monitored by spectrometric methods through a detection window associated with the porous bed. The creation of undesired channels, cavities and air inclusions will increase the noise level for detection and thus also reduce sensitivity and reproducibility.
- During transportation of microfluidic devices that comprises porous beds, there is a significant risk that solid phase material may escape from the microcavity in which it is originally placed. The risk for losses of dispensed reagents and analyte by reactions with escaped solid phase material at undefined locations within a microchannel structure is apparent. This kind of problem is most severe if the bed is built up of particles.

GY 0068SE  
2004-01-29

5

**OBJECTS OF THE INVENTION**

The objects are to provide improved microfluidic devices that solve the problems discussed above. The objects thus comprise to provide microfluidic devices

- 5 comprising solid phase material in a dry state that after storage and transportation of the device can be reconstituted to wet beds with essentially the same performance as wet beds of the same solid phase material not having being transformed to the dry state. If the solid phase material comprises an immobilized reactant, its activity, e.g. binding activity such as capacity, shall be essentially unchanged by transformation to
- 10 the dry state, storage, transportation and reconstitution. This in particular applies to activity under flow conditions. The objects include providing methods for manufacturing the devices and use of the devices for separation and/or assay purposes, among others.

**15 THE INVENTION**

It has now been discovered that there are certain compounds and/or combinations of compounds that when intimately mixed with a solid phase material will reduce adverse effects of predispensing, drying, storage, transportation, reconstitution etc of solid phase materials intended to be used as minute porous beds in microfluidic

- 20 devices. These negative effects are for example:

- a) unacceptable formation of channels, cavities, air inclusions etc and/or,
  - b) escape of solid phase material from a desired location within a microchannel structure, and/or
  - c) reduction of the binding activity of an immobilized reactant, e.g. affinity
- 25 reactant

This kind of compound or combination of compounds will henceforth be called "bed-preserving agent" or simply "preserver" since they will assist in restoring a dried solid phase material to an efficient wet porous bed. A bed-preserving agent is simply included in the liquid phase of a wet solid phase material before drying/dehydration.

- 30 Drying can take place inside or outside the microfluidic device. By using the proper microfluidic distribution manifold, we have found that the accuracy for the formation of reconstituted wet beds of predetermined volume can be further increased in each microchannel structures/reaction microcavity connected to the manifold. Inter-channel

GY 0068SE

6

2004-01-29

2004-0129

Huvudfaxen Kassar

variations due to drying, storage, transportation and/or reconstitution of preloaded solid phase materials can easily be held at a minimum.

It has also been discovered that common flow control as defined in WO 0275312 is

- 5 beneficial for increasing the accuracy in restoring wet porous bed volumes in parallel in reaction microcavities of at least a subset of microchannel structures of a microfluidic device. Centrifugal force, for instance, is useful for improving the yield of efficient porous beds if applied for settling and restoring the beds.

10 **FIRST ASPECT: MICROFLUIDIC DEVICE**

This aspect is a microfluidic device that comprises one, two or more microchannel structures, each of which comprises a reaction microcavity intended for retaining a solid phase material in the form of a porous bed. The device is characterized in that each microchannel structure comprises a reaction microcavity with a hydrophilic solid

- 15 phase material in a dry state that comprises one or more compounds that act as bed-preserving agents and secure that an acceptable wet porous bed is restored after a reconstitution liquid has passed the dry state solid phase material. The bed preserving agent(s) are capable of

- a) stabilizing the solid phase material possibly containing an immobilized reactant  
20 (e.g. an affinity reactant) during  
(i) transformation of a wet state of the solid phase material to a dry state, and/or  
(ii) a subsequent storage and/or transportation, and/or  
b) assisting in the reconstitution of the dry state to a wet porous bed.

- 25 The term "acceptable wet porous bed" means that the experimental results from the bed can be used, i.e. the bed is functional. The term "unacceptable" means that the experimental results are discarded. The bed-preserving agent used thus increases the probability for obtaining acceptable beds. The use of the principles of the invention may thus assist in increasing the yield of functional beds/microchannel structure on a  
30 microfluidic device to become  $\geq 70\%$ , such  $\geq 80\%$  or  $\geq 90\%$  or  $\geq 95\%$  or  $\geq 98\%$  of the total number of beds of a microfluidic device.

GY 0068SE

7

2004-01-29

2004-0129

Huvudtaxon Klassan

By the term "dry state" is meant that the amount of remaining liquid after drying is  $\leq$

50 %, such as  $\leq 30$  % or  $\leq 20$  % or  $\geq 10$  % of the amount of liquid present in the solid phase material when saturated with the liquid concerned (with no free liquid layer appearing on top of the bed). In many cases this means that the amount of liquid in the

- 5 solid phase material after drying and/or storage is  $\leq 20$  % (w/w), such as  $\leq 10$  % or  $\leq 5$  %. The liquid referred to is typically water.

### Bed-preserving agents (additives)

- The damages of a porous bed during drying/dehydration and storage typically depend
- 10 on stresses induced during transformation from a wet state to a dry state in the similar manner as for biologically active material. The choice of bed-preserving agent will depend on the conditions for drying, the solid phase material, kind of immobilized reactant etc. The same compound(s) may act as bed-preserving agent for one solid phase material and/or immobilized reactant but negatively affect other combinations.
- 15 It will thus be extremely important to test individual preserver candidates [either as single compounds or as combination(s) of compounds] and conditions for the transformation to the dry state and/or the conditions for storage and/or reconstitution before a candidate is used for a particular solid phase material. Testing is typically by trial and error and may include
- 20 a) physical inspection of the bed to find undesired channels, cavities and air inclusions, and/or
- b) determination of through flow properties, activity of an immobilized reactant, etc. Determination of the activity of the immobilized reactant/ligand may include determination of i) the activity profile in the flow direction and/or perpendicular to the
- 25 flow direction (i.e. the distribution of activity in the bed), ii) the total activity of the bed etc, for instance by testing the bed behavior in a standard type of assay or in an actual future use of the porous bed. If the immobilized reactant is an affinity reactant that is able to capture a solute, the distribution of the solute in the bed after adsorption may be used to find abnormal local behavior caused by channels, cavities, air
- 30 inclusions or local inactivation of the reactant, for instance. The total amount of adsorbed solute may give a total view, e.g. a measure of the mean condition of the immobilized reactant after reconstitution. Adsorption in this context is preferably performed under flow conditions, i.e. a liquid containing the solute is allowed to flow



GY 0068SE

8

2004-0129

2004-01-29

Huvudkontor Kassar

through the porous bed. These kinds of testing typically include a comparison with a standard bed and/or standard behavior that may be given by

- a) tabulated values,
- b) preset specifications,
- 5 c) the behavior of a bed prepared from non-lyophilized/non-dried solid phase material of the same kind as the lyophilized/dried solid phase material to be tested, etc.

The substeps during which the risk for damages is most significant are primarily the  
10 drying step (dehydration step) and the storage as such. In the case freeze-drying is part of the transformation also the freezing step may cause significant damages. For biologically active material, it is well known that particular stabilisators may be required for each substep. Hence, cryostabilisators refer to freezing, lyostabilisators to dehydration/drying and long term stabilisators to storage. See for instance Arakawa et  
15 al (Advanced Drug Delivery Reviews 46 (2001) 307-326). In the context of the present invention the analogous categorization is used for bed-preserving agents.

Compounds that assist in the reconstitution of the dry solid phase material to the wet porous bed are called bed-reconstitution agents and are also bed-preserving agents.

20

A bed-preserving agent may be active in relation to at least one up to all of the steps: drying/dehydration, freezing, storage and reconstitution. The efficiency of a particular agent will depend on the conditions for the particular step, solid phase material and/or immobilized reactant to be stabilized.

25

A bed-preserving agent that is useful in the present invention typically is hydrophilic in the sense that it is water-soluble. Many bed-preserving agents thus exhibit one or more heteroatoms selected from oxygen, nitrogen and sulphur, typically with a ratio between the total number of carbon atoms and the total number of oxygen, nitrogen

30 and sulphur atoms which is  $\leq 6$ , such as  $\leq 4$  or  $\leq 2$ .

Typical bed-preserving agents may be found in the group consisting of compounds exhibiting a) carbohydrate structure which also includes sugar alcohol structure, b)

GY 0068SE

9

2004-0129

polyhydroxy structure (i.e. organic polyols which also includes polyhydroxy polymers), c) amino acid structure including peptide structure and imino acid structure, d) inorganic salts, e) organic salts in particular carboxylates, f) amine structure including amino acid structure and ammonium structure, h) etc.

5

Suitable compounds with carbohydrate structures may be found amongst sucrose, lactose, glucose, trehalose, maltose, isomaltose, cellobiose, inositol, ethylene glycol, glycerol, sorbitol, xylitol, mannitol, polyethylene glycol possibly substituted in one or both of its end, dextran, maltodextrin, monosaccharides, disaccharides,

- 10 polysaccharides including oligosaccharides etc. Compounds with carbohydrate structures are typically also polyols.

Suitable polyols may be found amongst polyhydroxy polymers, such as polysaccharides, polyvinylalcohol possibly partially substituted on its hydroxy groups

- 15 for instance with acetate or lower hydroxy alkyl groups ( $C_{2-4}$ ), poly (lower hydroxy alkyl ( $C_{2-4}$ ) acrylate) polymers and corresponding poly methacrylate polymers etc, and monomeric compounds having two or more hydroxy groups. In a typical polyol each hydroxy group is attached directly to an  $sp^3$ -hybridised carbon.

- 20 Suitable polymers are typically found amongst polymers that have a plurality of functional groups comprising a heteroatom selected from oxygen and nitrogen. Relevant functional groups are  $-O(CH_2CH_2O)_n-$  where  $n$  is  $\geq 2$  such as  $\geq 5$ , amido such as  $-CONH-$  or  $-CONH_2$  where H may be replaced with a suitable hydrophilic organic group, hydroxy (OH), ester ( $-COOR$ , where R is a suitable hydrophilic organic group), etc. Specific examples are polyethylene glycol, dextran and other
- 25 polysaccharides, polyvinylpyrrolidone, polypeptides, the poly acrylate and methacrylate polymers mentioned above, the polyvinyl alcohols mentioned above etc.

- In the bed-preserving candidates mentioned above the term polymer also includes
- 30 copolymer in which the specific polymer structure mentioned is a part

Bed-preserving agents that are lyostabilisators are believed to act during the drying/dehydration step by replacing water bound to the solid phase material to be

GY 0068SE

10

2004-0129

Huvudtaxen Kassar

stabilized. These bed-preserving agents thus primarily are found among compounds that may participate in hydrogen bonding/coordination with the solid phase material. With the present knowledge the most typical candidates for lyostabilization are found amongst polyols (including diols, triols etc), e.g. with a polymeric structure and/or

5 carbohydrate structure (oligomeric is included in polymeric). In the case the solid phase material comprises an immobilised reactant, e.g. with peptide structure, it is believed that the most efficient candidates have carbohydrate structure with preference for disaccharides and found amongst sucrose, lactose, glucose, trehalose, maltose, isomaltose, cellobiose etc.

10

Many times suitable bed-preserving agents, such as lyostabilisators and stabilisators for long term storage, may exist in a glassy state at an ordinary temperature. An ordinary temperature in this context means at least a part of the interval + 15-35°C. Typically this means a glass transition temperature  $\geq + 25^{\circ}\text{C}$  or  $\geq + 30^{\circ}\text{C}$  or  $\geq + 35^{\circ}\text{C}$ .

15

The bed-preserving agents that are present in the dry state of a solid phase material are typically non-volatile. This does not exclude having volatile cryostabilisators included during lyophilization.

## 20 Protectants (additives)

The solid phase material that is in a dry state may also contain one or more so-called protectants that inhibit undesired chemical reactions of the solid phase material and/or the immobilized reactant. Suitable protectants are found amongst free radical scavengers, antioxidants, reducing agents etc.

25

## Other additives

The solid phase material in a dry state may also contain an appropriate buffer, such as a buffer with non-volatile buffering components, e.g. with at least one or two of the buffering components being anionic, such as in phosphate buffers, citrate buffers etc.

30 Also other buffers may be used. The buffering components typically provide an elevated buffer capacity within an appropriate pH interval of the range of pH 1-13 with preference for the range 3-11. For lyophilized solid phase materials, phosphate buffers, in particular with potassium as counter-ion, are preferred.

GY 0068SE  
2004-0129

11

Ink. t. Patent- och reg.verket

2004-01-29

Huvudföreläsning

Other additives such as one or more antimicrobial agents may also be included, e.g. a bacteriostat, a bacteriocid, a virucid etc.

- 5 A possible bulking agent may also be included as an additive. The bulking agent may have bed-preserving effects on the solid phase material as discussed above for bed preserving agents in general.

- 10 Microcavity adherence agents (a kind of bed-preserving agents) cause the solid phase material to be retained in a reaction microcavity and therefore assist in restoring a dry state solid phase material to a wet porous bed. This kind of agents acts by causing particles to adhere to each other and/or to the inner walls of a reaction microcavity. Microcavity adherence agents may be found amongst the bed-preserving candidates discussed above, for instance amongst those that exhibit carbohydrate and/or
- 15 polymeric structure.

- The various additives (bed preserving agents, buffer substances, protectants, bulking agents etc) are typically present in the solid phase material that is in the dry state in an amount in the interval of 0.001 - 25 %, such as  $\geq 0.01\%$  or  $\geq 0.1\%$  and/or  $\leq 10\%$  or  $\leq$
- 20 1 %. These intervals apply to each individual additive as well as to the total amount of additive with the proviso that the total amount should not exceed the upper limit of an interval. The determination of optimal ranges of efficient amounts and sufficient bed-preserving effects of individual bed-preserving agents needs experimental testing as discussed above. The %-figures refer to the weight of the additive(s) relative to the
- 25 total weight of solid phase material in the dry state.

- Additives (stabilisators, buffer substances, protectants, antimicrobials and/or bulking agents) are typically soluble in aqueous media so that they easily can be removed from the reconstituted porous bed.

30

#### Reaction microcavity and the solid phase material.

The reaction microcavity is defined as the part of a microchannel structure in which the solid phase is present. This means that for solid phases in the form of porous beds,

GY 0068SE

12

2004-01-29

2004-0129

the bed volume and the reaction microcavity will coincide and have the same volume.

If the solid phase is the inner wall of a microconduit, the reaction microcavity is defined as the volume between the most upstream and the most downstream end of the solid phase.

5

The reaction microcavity is typically a straight or bent microconduit that may or may not be continuously widening and/or narrowing. On the same device all reaction microcavities typically have essentially the same shape and/or size. In a microfluidic device that comprises reaction microcavities according to the invention that differ in shape and/or size, the reaction microcavities/microchannel structures may be divided into groups where each group contains reaction microcavities that are not present in any of the other groups. Each group may be placed in a subarea of the device that is separate from the subareas of other groups.

15

The reaction microcavity has at least one cross-sectional dimension that is  $\leq 1,000 \mu\text{m}$ , such as  $\leq 500 \mu\text{m}$  or  $\leq 200 \mu\text{m}$  (depth and/or width). The smallest cross-sectional dimension is typically  $\geq 5 \mu\text{m}$  such as  $\geq 25 \mu\text{m}$  or  $\geq 50 \mu\text{m}$ . The total volume of the reaction microcavity is typically in the nl-range, such as  $\leq 5,000 \text{ nl}$ , such as  $1,000 \text{ nl}$  or  $\leq 500 \text{ nl}$  or  $\leq 100 \text{ nl}$  or  $\leq 50 \text{ nl}$  or  $\leq 25 \text{ nl}$ .

20

The porous bed is a) a population of porous or non-porous particles, or b) a porous monolith.

A monolithic bed may be in the form of a porous membrane or a porous plug.

25

The term "porous particles" have the same meaning as in WO 0275312 (Gyros AB).

Suitable particles are spherical or spheroid (beaded) or non-spherical. Suitable mean diameters for particles used as solid phases are typically found in the interval of 1-100  $\mu\text{m}$  with preference for mean diameters that are  $\geq 5 \mu\text{m}$ , such as  $\geq 10 \mu\text{m}$  or  $\geq 15 \mu\text{m}$  and/or  $\leq 50 \mu\text{m}$ . Also smaller particles can be used, for instance with mean diameters down to  $0.1 \mu\text{m}$ . The outlet of the reaction microcavity and the particles should match

30

GY 0068SE

13

2004-01-29

2004-0129

Huvudföreläsning

each other so that the particles can be retained in the reaction microcavity. Certain kinds of particles, in particular particles of colloidal dimension, may agglomerate. In these cases the size of the agglomerate should be in the intervals given even if the agglomerating particles as such are below. See for instance WO 0275312 (Gyros AB).

- 5 Diameters refer to the "hydrodynamic" diameters.

Particles to be used may be monodisperse (monosized) or polydisperse (polysized) in the same meaning as in WO 0275312 (Gyros AB).

- 10 The solid phase material may or may not be transparent.

The base material of a solid phase may be made of inorganic and/or organic material. Typical inorganic materials comprise glass and typical organic materials comprise organic polymers. Polymeric materials comprise inorganic polymers, such as glass,

- 15 and organic polymers that may be of synthetic or biological origin (biopolymers). The term biopolymer includes semi-synthetic polymers in which there is a polymer backbone derived from a native biopolymer. Typical synthetic organic polymers are cross-linked and are often obtained by the polymerisation of monomers comprising polymerisable carbon-carbon double bonds. Examples of suitable monomers are
- 20 hydroxy alkyl acrylates and corresponding methacrylates, acryl amides and methacrylamides, vinyl and styryl ethers, alkene substituted polyhydroxy polymers, styrene, etc. Typical biopolymers may or may not be cross-linked. In most cases they exhibit a carbohydrate structure, e.g. agarose, dextran, starch etc.

- 25 The term "hydrophilic" in the context of a porous bed contemplates ability to absorb water when contacted with water. The expression also means that the inner surfaces of the bed that is in contact with water during the absorption shall expose a plurality of polar functional groups which each has a heteroatom selected amongst oxygen and nitrogen, for instance. Appropriate functional groups can be selected amongst
- 30 hydroxy groups, ethylene oxide groups  $(-X-[-CH_2CH_2O-])_n$  where  $n$  is an integer  $> 1$  and  $X$  is nitrogen or oxygen), amino groups, amide groups, ester groups, carboxy groups, sulphone groups etc, with preference for those groups that are essentially uncharged independent of pH, for instance within the interval of 2-12. For solid phase

GY 0068SE

14

2004-0129

Huvudkassan Kassar

materials in particle form this means that at least the outer surfaces of the particles have to exhibit polar functional groups. The hydrophilic functional groups may be present on or be a part of so called extender arms (tentacles).

- 5 If the base material of a solid phase material is hydrophobic or not sufficiently hydrophilic, e.g. is based on a styrene (co)polymer, the surfaces that are to be in contact with an aqueous liquid may be hydrophilized. Typical protocols comprise coating with a compound or mixture of compounds exhibiting polar functional groups of the same type as discussed above, treatment by an oxygen plasma etc.

10

The solid phase material may be swellable or not swellable in water or other aqueous liquid media. Swellable materials are likely to be more prone to give problem related to (a) shrinkage, and inhomogeneous packing and/or through flow after reconstitution and/or (b) escape of dry particles during storage and transportation. The term

- 15 "swellable" in this context means that an increase in volume of the material (particles as such or a monolith) can be detected or is  $\geq 10$  or  $\geq 75$  % when the material in the dry state (as defined above) is contacted with excess water. The temperature referred to is typically  $+25^{\circ}\text{C}$ .

- 20 The solid phase material may be rigid or elastic.

The solid phase material may or may not contain an immobilized reactant that is capable of participating in an organic, an inorganic, a biochemical reaction etc.

Depending on the circumstances and the kind of reactant and the solutes, the

- 25 interaction may be part of a separation process, a catalytic reaction, a solid phase synthesis etc.

This reactant will now be illustrated with an affinity reactant that is an affinity counterpart ( $\text{AC}_\text{S}$ ) to a solute (S) and capable of forming an affinity complex ( $\text{AC}_\text{S}\text{-S}$ )

- 30 with the solute. Affinity bonds typically are based on: (a) electrostatic interactions, (b) hydrophobic interactions, (c) electron-donor acceptor interactions, and/or (d) bioaffinity binding.

GY 0068SE

15

2004-01-29

2004-0129

Bioaffinity binding typically is complex and comprises a combination of interactions. Huvudförfaren Kossan

An immobilized affinity counterpart (ACs) may thus:

- (a) be electrically charged or chargeable, i.e. contains positively charged nitrogen (e.g. primary, secondary, tertiary or quaternary ammonium groups, and amidinium groups) and/or negatively charged groups (e.g. carboxylate groups, phosphate groups, phosphonate groups, sulphate groups and sulphonate groups); and/or
- (b) comprise one or more hydrocarbyl groups and other hydrophobic groups; and/or
- (c) comprise one or more heteroatoms (O,S,N), possibly linked to hydrogen and/or
- (d) comprise a combination of features (a)-(c).

A bioaffinity reactant/ligand is a member of a bioaffinity pair. Typical bioaffinity pairs are a) antigen/hapten and an antibody, b) complementary nucleic acids, c) immunoglobulin-binding protein and immunoglobulin (for instance IgG or an Fc-part thereof and protein A or G), d) lectin and the corresponding carbohydrate, e) biotin and (strept)avidin, e) members of an enzymatic system (enzyme-substrate, enzyme-cofactor, enzyme-inhibitor etc), f) an IMAC group and an amino acid sequence containing histidyl and/or cysteinyl and/or phosphorylated residues (i.e. an IMAC motif), etc. Antibody includes antigen binding fragments and mimetics of antibodies. The term "bioaffinity pair" includes also affinity pairs in which one or both of the members are synthetic, for instance mimicking one or both of the members of a native bioaffinity pair. The term IMAC stands for an immobilized metal chelate.

The term "affinity reactant" also includes a reactant that is capable of reversible covalent binding, for instance by disulfide formation. This kind of reactants typically exhibits a HS- or a -S-SO<sub>n</sub>- group (n = 0,1 or 2, free valences bind to carbon). See US 5,887,997 (Batista), US 4,175,073 (Axén et al), and 4,563,304 (Axén et al).

The immobilized reactant/ligand (affinity reactant) may also be a catalytic system or a member of a catalytic system, such as a catalyst, a cocatalyst, a cofactor, a substrate or cosubstrate, an inhibitor, a promotor etc. For enzymatic systems the corresponding members are enzyme, cocatalyst, cofactor, coenzyme, substrate, cosubstrate etc. The



GY 0068SE

16

1994-01-29

2004-0129

term "catalytic system" also includes linked catalytic systems, for instance a series of systems in which the product of the first system is the substrate of the second catalytic system etc and whole biological cells or part of such cells.

- 5 The immobilized affinity reactant ( $AC_s$ ) should be selected to have the appropriate selectivity and specificity for binding the solute to the solid phase material in relation to an intended application. General methods and criteria for the proper selection of affinity reactants and reaction conditions are well known in the field.
- 10 The affinity constant ( $K_{S-AC} = [S][AC_s]/[S-AC_s]$ ) for the formation of the complex comprising the immobilized affinity reactant ( $AC_s$ ) and the solute (S) is an important criterion for optimizing an application and varies depending on application. For affinity assays the affinity constant is typically  $\leq 10^{-8}$  mole/l or  $\leq 10^{-9}$  mole/l. This kind of assays typically includes that the solute is reacted with immobilized  $AC_s$
- 15 under flow conditions and related to the amount of an analyte in an animal or biological sample (animal or biological sample include samples from mammals, such as human and other animal patients, and from experimental animals). This does not exclude that affinity counterparts having weaker affinities may be used for this kind of samples, other samples and affinity assays, and other applications. Thus depending on
- 20 application the affinity constant may be relatively large, such as up to  $10^{-3}$  mole/l or up to  $10^{-4}$  mole/l or up to  $10^{-5}$  or up to  $10^{-7}$  mole/l, or relatively low, such as less than  $10^{-8}$  mole/ or less than  $10^{-11}$  mole/l.

The techniques for immobilization of a reactant/ligand may be selected amongst

25 techniques that are commonly known in the field. The linkage to the solid phase material may thus be via covalent bonds, affinity bonds (for instance biospecific affinity bonds), physical adsorption etc.

Immobilization via affinity bonds may utilize an immobilizing affinity pair in which

30 one of the members (immobilized ligand or L) is firmly attached to the solid phase material, for instance covalently. The other member (immobilizing binder, B) of the pair is used as a conjugate (immobilizing conjugate) comprising binder B and the affinity counterpart  $AC_s$  to the solute S. Examples of immobilizing affinity pairs are

GY 0068SE

17

2004-01-29

2004-0129

Hanselluxen Kasson

a) streptavidin/avidin/ neutravidin and a biotinylated reactant (or vice versa), b) antibody and a haptenylated reactant (or vice versa), c) an IMAC group and an amino acid sequence containing histidyl and/or cysteinyl and/or phosphorylated residues (i.e. an IMAC motif) linked to a reactant, etc.

5

The term "conjugate" primarily refers to covalent conjugates, such as chemical conjugates and recombinantly produced conjugates (where both the moieties have peptide structure). The term also includes so-called native conjugates, i.e. affinity reactants exhibiting two binding sites that are spaced apart from each other, with affinity directed towards two different molecular entities, for instance a native antibody that comprises species and class-specific determinants on one side of the molecule and antigen/hapten-binding sites on another side.

It is believed that it is advantageous that the immobilized ligand L has two or more binding sites for the immobilizing binder B, and/or the immobilizing binder B has one, two or more binding sites for the ligand L (or vice versa).

Preferred immobilizing affinity pairs (L and B) typically have affinity constants ( $K_{L-B} = [L][B]/[L-B]$ ) that are at most equal to or  $\leq 10$  times or  $10^2$  times or  $\leq 10^3$  times larger than the corresponding affinity constant for streptavidin and biotin. This typically will mean affinity constants that roughly are  $\leq 10^{-13}$  mole/l,  $\leq 10^{-12}$  mole/l,  $\leq 10^{-11}$  mole/l and  $\leq 10^{-10}$  mole/l, respectively. The preference is to select L and B amongst biotin-binding compounds and streptavidin-binding compounds, respectively, or vice versa.

25

The affinity constants discussed above refer to values obtained by a biosensor (surface plasmon resonance) from Biacore (Uppsala, Sweden), i.e. with the affinity reactant (ACs and L) immobilized to a dextran-coated gold surface.

At least one of the members of an affinity pair, in particular a bioaffinity pair, to be used in the present invention typically exhibits a structure selected amongst: a) amino acid structure including peptide structure such as poly and oligopeptide structure, b) carbohydrate structure, c) nucleotide structure including nucleic acid structure, d)

GY 0068SE

18

2004-0129

Huvudkassan

lipid structure such as steroid structure, triglyceride structure etc. The term affinity pair in this context refers to the immobilizing affinity pair (L and B), the immobilized affinity reactant and the solute (AC<sub>5</sub> and S) and other affinity pairs that may be used.

- 5 The solid phase material that is in a dry state may alternatively be in activated form. In other words ready for direct covalent immobilization by reaction with a functional group of a desired reactant. The functional group that can be used on the desired reactant is typically selected amongst electrophilic and nucleophilic groups and depends on whether or not the activated group is nucleophilic or electrophilic, respectively. Examples of functional groups that may be used are amino groups and other groups comprising substituted or unsubstituted -NH<sub>2</sub>, carboxy groups (-COOH/-COO<sup>-</sup>), hydroxy groups, thiol groups, keto groups etc.

#### Other features of the microfluidic device

- 15 A microchannel structure of the microfluidic device may comprise one, two, three or more functional parts selected among: a) inlet arrangement comprising for instance an inlet port/inlet opening, possibly together with a volume-metering unit, b) microconduits for liquid transport, c) reaction microcavity; d) mixing microcavity; e) unit for separating particulate matters from liquids (may be present in the inlet arrangement), f) unit for separating dissolved or suspended components in the sample from each other, for instance by capillary electrophoresis, chromatography and the like; g) detection microcavity; h) waste conduit/microcavity; i) valve; j) vent to ambient atmosphere; etc. A functional part may have more than functionality, e.g. reaction microcavity and a detection microcavity may coincide. Various kinds of functional units in microfluidic devices have been described by Gyros AB/Amersham Pharmacia Biotech AB: WO 9955827, WO 9958245, WO 02074438, WO 0275312, PCT/SE02/01539, PCT/SE02/01701 and by Tecan/Gamera Biosciences: WO 0187487, WO 0187486, WO 0079285, WO 0078455, WO 0069560, WO 9807019, WO 9853311.

30

In advantageous forms a reaction microcavity intended for a hydrophilic porous bed is connected to one or more inlet arrangements (upstream direction), each of which comprises an inlet port and at least one volume-metering unit. In one advantageous

GY 0068SE

19

2004-0129

variant, there is one separate inlet arrangement per microchannel structure and reaction microcavity intended to contain the solid phase material. In another

advantageous variant, the inlet arrangement is common to all or a subset of microchannel structures and reaction microcavity intended to contain the solid phase material and comprises a common inlet port and a distribution manifold with one volume-metering unit for each microchannel structure/reaction microcavity of the subset. In both variants, each of the volume-metering units in turn is communicating with downstream parts of its microchannel structure/reaction microcavity.

Microchannel structures linked together by a common inlet arrangement and/or common distribution manifold define a group of the microchannel structures of the device.

Typical inlet arrangements have been presented in WO 0274438 (Gyros AB), WO 0275312 (Gyros AB), WO 0275775 (Gyros AB) and WO 0275776 (Gyros AB).

The microfluidic device may also comprise other common microchannels/micro conduits connecting different microchannel structures. Common channels including their various parts such as inlet ports, outlet ports, vents, etc., are considered part of each of the microchannel structures they are communicating with.

Common microchannels make it possible to construe microfluidic devices in which the microchannel structures form networks. See for instance US 6,479,299 (Caliper).

Each microchannel structure has at least one inlet opening for liquids and at least one outlet opening for excess of air (vents) and possibly also for liquids.

The microfluidic device may also comprise microchannel structures that have no reaction microcavity for retaining a solid phase material according to the invention.

The microfluidic device contains a plurality of microchannel structures/device intended to contain the solid phase according to the invention. Plurality in this context means two, three or more microchannel structures and typically is  $\geq 10$ , e.g.  $\geq 25$  or  $\geq 90$  or  $\geq 180$  or  $\geq 270$  or  $\geq 360$ . As discussed above the microchannel structures of a

GY 0068SE

20

Huvudfunkt. Kassen

2004-0129

device may be divided in groups, each of which may for instance be defined by the size and/or shape of the reaction microcavity, by a common microchannel, such as a common inlet arrangement or manifold etc. The number of microchannel structures in a group is typically in the interval 1-99 %, such as 5-50 % or 5-25 % or 10-50%, of the total number of microchannel structures of the device. This typically means that each group typically comprises from 3-15 or 3-25 or 3-50 microchannel structures. Each group may be located to a particular area of the device.

Different principles may be utilized for transporting the liquid within the microfluidic device/microchannel structures between two or more of the functional parts described above. Inertia force may be used, for instance by spinning the disc as discussed in the subsequent paragraph. Other forces are capillary forces, electrokinetic forces, non-electrokinetic forces such as capillary forces, hydrostatic pressure *etc.*

The microfluidic device typically is in the form of a disc. The preferred formats have an axis of symmetry ( $C_n$ ) that is perpendicular to the disc plane, where  $n$  is an integer  $\geq 2$ , 3, 4 or 5, preferably  $\infty$  ( $C_\infty$ ). In other words the disc may be rectangular, such as squaric, and other polygonal forms but is preferably circular. Once the proper disc format has been selected centrifugal force may be used for driving liquid flow.

Spinning the device around a spin axis that typically is perpendicular or parallel to the disc plane may create the necessary centrifugal force. In the most obvious variants at the priority date, the spin axis coincides with the above-mentioned axis of symmetry.

For preferred centrifugal-based variants, each microchannel structure comprises one upstream section that is at a shorter radial distance than a downstream section relative to a spin axis. The reaction microcavity intended for the porous bed is then at a radial position intermediary to the two sections.

If centrifugal force is used for the formation and/or reconstitution of a particle bed and/or for driving liquid flow through the bed, the reaction microcavity is typically oriented with the flow direction radially outwards from the spin axis.

GY 0068SE

21

2004-0129

Huvuduxen Kassar

The preferred devices are typically disc-shaped with sizes and forms similar to the conventional CD-format, e.g. sizes that are in the interval from 10% up to 300 % of the conventional CD-radii. The upper and/or lower sides of the disc may or may not be planar.

5

Microchannels/microcavities of a microfluidic devices may be manufactured from an essentially planar substrate surface that exhibits the channels/cavities in uncovered form that in a subsequent step are covered by another essentially planar substrate (lid). See WO 9116966 (Pharmacia Biotech AB) and WO 0154810 (Gyros AB). Both

10 substrates are preferably fabricated from plastic material, e.g. plastic polymeric material.

The fouling activity and hydrophilicity of inner surfaces should be balanced in relation to the application. See for instance WO 0147637 (Gyros AB).

15

The terms "wettable" (hydrophilic) and "non-wettable" (hydrophobic) contemplate that a surface has a water contact angle  $\leq 90^\circ$  or  $\geq 90^\circ$ , respectively. In order to facilitate efficient transport of a liquid between different functional parts, inner surfaces of the individual parts should primarily be wettable, preferably with a contact

20 angle  $\leq 60^\circ$  such as  $\leq 50^\circ$  or  $\leq 40^\circ$  or  $\leq 30^\circ$  or  $\leq 20^\circ$ . These wettability values apply for at least one, two, three or four of the inner side-walls of a microconduit. In case one or more of the side-walls have a higher water contact angle this can be compensated for by a lower water contact angle for the remaining side-wall(s). The wettability, in particular in inlet arrangements should be adapted such that an aqueous

25 liquid will be able to fill up an intended microcavity by capillarity (self suction) once the liquid has started to enter the cavity. A hydrophilic inner surface in a microchannel structure may comprise one or more local hydrophobic surface breaks in a hydrophilic inner side-wall, for instance for introducing a passive valve, an anti-wicking means, a vent solely function as a vent to ambient atmosphere etc. See for

30 instance WO 9958245 (Gyros AB) and WO 0274438 (Gyros AB).

GY 0068SE

22

2004-0129

Contact angles refer to values at the temperature of use, typically +25°C, are static and can be measured by the method illustrated in WO 0056808 (Gyros AB) and WO 0147637 (Gyros AB).

**5 SECOND ASPECT: METHOD FOR THE TRANSFORMATION OF A PLURALITY OF WET POROUS BEDS TO A DRY/DEHYDRATED STATE THAT POSSIBLY IS RECONSTITUTED TO A PLURALITY OF WET POROUS BEDS .**

This aspect is a method as the defined in the heading of this section. The method is characterized in comprising the steps of:

- 10 i) providing a microfluidic device comprising a plurality of microchannel structures each of which comprises a reaction microcavity containing a hydrophilic porous bed saturated with a liquid containing a bed-preserving agent,
- ii) transforming the bed in each reaction microcavity to a solid phase material
- 15 that is in a dry and/or dehydrated state,
- iii) possibly reconstituting the solid phase material obtained in step ii) to the wet porous beds of the microchannel structures.

This aspect also concerns a method for reducing the inter-channel variation in a

20 microfluidic device with respect to performance of reconstituted porous beds.

The solid phase material may or may not exhibit a reactant that can interact with a solute. Various characteristics are discussed below and elsewhere in this specification.

25 Step (iii) is preferably carried out under flow conditions, for instance with residence time and flow rates through the bed as discussed for the third aspect of the invention.

Porous particle beds can be created by flowing a dispersion of particles through all or one or more subsets of the reaction microcavities of the microfluidic device. The

30 particles will then settle and form a porous bed at the outlet end of each microcavity. Bed formation may be facilitated by the use of gravity and/or the use of centrifugal force, the latter preferably acting along the flow direction of each reaction microcavity. The desired additives as discussed above are present in the liquid

GY 0068SE

23

2004-01-29

2004-0129  
dispersion and/or introduced by passing a liquid containing the additives through the bed after it has been formed. The microfluidic device together with the beds saturated with a liquid containing the additives is saved until transformation to the dry state.

5 A porous monolithic bed is typically introduced during the manufacture of the device, for instance

- a) by polymerization, or
- b) by placing ready-made porous monoliths

in each of at least a subset of the reaction microcavities of the microfluidic device.

10

In alternative a) the preferred variant is to carry out the polymerization with the reaction microcavity and the corresponding microchannel structure in an enclosed form. In alternative b) the preferred variant is to insert the monolith while at least the reaction microcavity is uncovered. After introduction of the porous bed and if needed

15 enclosing the microcavity, the beds are saturated with a solution comprising the additives discussed above and saved until transformation to the dry state.

Transformation of the beds to the dry state may be accomplished by removing the liquid under subatmospheric pressure, for instance below and/or above the freezing  
20 point of the liquid they are saturated with. Removal under subatmospheric pressure and below the freezing point typically means lyophilization (lyophilization).  
Alternatively liquid is removed from the settled dispersion under ambient atmosphere with or without warming. In the case the device is intended for using centrifugal force for driving liquid flow so called spin-drying may be employed. See the experimental  
25 part.

The reconstitution of the wet porous beds means that a reconstitution liquid is allowed to flow through each of the reaction microcavities containing solid phase material in a dry state. See the experimental part.

30

An important tool for treating the solid phase material equal in several structures is to provide each microchannel structure with an inlet arrangement that in preferred variants is common to a group of microchannel structures/reaction microcavities as



GY 0068SE

24

2004-0129

Mikrofluidic Korean

discussed for the first aspect for parallel dispensation of solid phase material and reconstituting and conditioning of porous beds. In order to accomplish the best benefits of the invention it is thereby important to provide inner surfaces of at least the inlet arrangements, distribution manifold, and/or individual volume-metering units with hydrophilic surface characteristics within the limits discussed elsewhere in this specification and the outlet of each volume-metering unit with a valve function that preferably is passive in the sense that it is without movable parts, for instance in the form of a local hydrophobic surface break.

### 10 THIRD ASPECT OF THE INVENTION. THE USE OF THE DEVICE.

The use of the innovative microfluidic devices comprises in general terms the steps of:

- (i) providing a microfluidic device according to the first aspect of the invention;
- 15 (ii) reconstituting the solid phase material that is in the dry state to a wet porous bed in a predetermined number of the microchannel structures /reaction microcavities, preferably under flow conditions,
- (iii) providing a liquid containing a solute in a position that is upstream to said wet porous bed in one or more of the microchannel structures containing  
20 the wet porous bed,
- (iv) transporting the liquid through said wet bed in at least one of said one or more microchannel structures.

Step (iii) comprises that the solute is formed within the device/microchannel structure or is dispensed to the microchannel structure. If applicable, formation is typically in a position upstream or within the bed. Dispensing is typically to a position upstream the bed and via an inlet port.

The transport during step (iv) comprises that interaction between the immobilized  
30 affinity counterpart AC<sub>s</sub> and the solute S may take place under static or flow conditions, i.e. with or without transport of the solute by a liquid flow passing through the reaction microcavities. We have previously found that more information may be gained under flow conditions (WO 0275312 (Gyros AB), for instance with the flow

GY 0068SE

25

2004-01-29

2004-0129

- rate and/or residence time adjusted to give conditions such that the distribution of bound solute in the solid phase will reflect the actual reaction rate or affinity between an immobilized affinity reactant, typically ACs, and a solute, typically solute S, with a minimum of perturbation by diffusion (non-diffusion limiting conditions). This also applies to the present invention but does not exclude that for applications where the primary interest is the total amount of bound/captured solute, capturing under flow conditions utilizing either diffusion limiting or non-diffusion limiting conditions can be used. The appropriate flow rate through the porous bed thus depends on a number of factors, e.g. the immobilized reactant and the solute and their sizes, the volume of the reaction microcavity, the porous bed including the solid phase material etc. Typically the flow rate should give a residence time of  $\geq 0.010$  seconds such as  $\geq 0.050$  sec or  $\geq 0.1$  sec with an upper limit that typically is below 2 hours such as below 1 hour. Illustrative flow rates are within 0.01-1000 nl/sec, such as 0.01-100 nl/sec and more typically 0.1 - 10 nl/sec. These flow rate intervals may be useful for bed volumes in the range of 1-200 nl, such as 1-50 nl or 1-25 nl. Residence time refers to the time it takes for a liquid aliquot to be in contact with the solid phase in the reaction microcavity.

#### Steps (iii) and (iv)

- These steps are performed in order to allow for an interaction between the solute and the porous bed to take place. As mentioned in the introductory part, the steps may be part of (a) separation method, and/or (b) a catalytic reaction, and/or (c) a solid phase synthesis.
- Separation comprises among others:
- capturing, i.e. the porous bed exhibits an affinity structure (affinity ligand, affinity reactant) with binding ability for the solute such that when a liquid containing the solute passes through the bed then the liquid without solute or with a reduced amount of the solute will appear as a eluate, and/or
  - size exclusion, i.e. the porous bed is more prone to retain smaller molecules compared to larger molecules, and/or
  - electrophoresis, i.e. the porous bed functions as anti-convection and/or anti-diffusion means, and/or

GY 0068SE  
2004-0129

26

2004-01-29

iv) immobilization of the solute on the solid phase material for later use of the solid phase material so modified in capturing, catalytic reactions and solid phase synthesis.

- 5 For capturing (alternative i), the solute is adsorbed to the solid phase material and forms an immobilized affinity complex comprising the affinity structure and the solute. For many separation protocols a combination of capturing, size exclusion, electrophoresis etc is utilized.
- 10 For immobilization (alternative iv), the starting solid phase exhibits an affinity structure ( $AC_s = L'$ ) that is a counterpart to a conjugate ( $B' - AC'_s = S$ ) which has two kinds of binding sites: one ( $B'$ ) directed towards the affinity structure ( $L'$ ) on the solid phase and the other one towards a solute ( $S'$ ).  $L'$ ,  $B'$ ,  $S'$  and  $AC'_s$  then correspond to  $L$ ,  $B$ ,  $S$  and  $AC_s$  and what has been said in the context of the first aspect for  $L$ ,  $B$ ,  $S$
- 15 and  $AC_s$  including affinity constants also applies here.

The separation may be part of a purification or enrichment protocol for a solute that is present in the liquid. The solute that is separated from the liquid may be a contaminant or the entity to be purified, enriched etc. The separation may also be part

20 of a synthetic protocol, preparative protocol, a cell based assay, various kinds of affinity assays including nucleic acid assays, immunoassays, enzyme assays etc.

An affinity assay utilizing a capturing step for binding a solute to a solid phase material typically contemplates characterization of a reaction variable involved in an

25 affinity reaction of the assay. Reaction variables in this context are mainly of two kinds 1) variables related to affinity reactants, and 2) reaction conditions. Variables related to affinity reactants have two main subgroups a) amounts including presence and/or absence, concentration, relative amounts, activity such as binding activity and enzyme activity, etc, and b) properties of affinity reactants including affinity as such,

30 e.g. affinity constants, specificities etc. See WO 0275312 (Gyros AB). The molecular entity for which a reaction variable of type 1 is characterized is called an analyte.

GY 0068SE

27

2004-01-29

2004-0129

Catalytic reactions in the context of the present invention comprises that the solid phase material exhibits one or more immobilized members (affinity structure, affinity

- ligand, affinity reactant) of the catalytic system utilized, while other members of the same system are solutes. The catalytic reaction comprises formation of an affinity  
5 complex between the immobilized member (affinity structure, affinity ligand, affinity reactant) and at least one of the solute members. At least one of the members corresponds to the substrate for the catalytic system. The reaction results in a product that typically has a different chemical composition and/or structure compared to the substrate. The product may or may not become immobilized to the bed during the  
10 reaction.

- The term "catalytic system" includes single catalytic system and more complex variants comprising a series of linked single enzyme systems, whole cells, cell parts exhibiting enzymatic activity etc. The bed may function as a catalytic reactor, such as  
15 an enzyme reactor.

- The step during which interaction with the solute occurs may be part of a catalytic assay, such as an enzyme assay, for characterizing one or more members of the catalytic system or other reaction variable (e.g. reaction condition). The assay may be  
20 for determining the activity of a particular catalyst, substrate, co-substrate, cofactor, co-catalyst etc in a liquid sample. The molecular entity/entities corresponding to the activity to be determined is/are called analyte/analytes. See for instance SE 0201310 (Gyros AB).

- 25 In the context of assays, the term analyte includes the entity to be characterized in an original sample as well as analyte-derived entities formed during the assay and being related quantitatively and the analyte in the original sample. The solute discussed above may be the original analyte or an analyte-derived entity.

- 30 Solid phase synthesis includes for instance polymer synthesis, such as oligopeptide and oligonucleotide synthesis and synthesis of other small molecules on a solid phase material. The immobilized reactant in used in polymer synthesis, for instance, may exhibit the structure of the corresponding monomer, such as nucleotide, carbohydrate,

GY 0068SE

28

-01- 2 9

2004-0129

amino acid structure, and mimetics of these structures. Synthesis of libraries of immobilized members of combinatorial libraries is also included. Such members have relatively low molecular weights (e.g. < 10,000 dalton including a possible spacer to a polymeric backbone).

5

**A MICROFLUIDIC DEVICE COMPRISING SEGMENTED POROUS BEDS (THE FOURTH ASPECT)**

A separate innovative aspect (4<sup>th</sup> aspect) is a microfluidic device that comprises one, two or more microchannel structures, each of which comprises a reaction microcavity in which a solid phase material in the form of a wet porous bed is retained. A reactant is exposed in immobilized form on the solid phase material and capable of interacting with a solute (S) in a liquid passing through the bed.

During experiments with different kinds of samples when carrying out experiments as outlined in this specification and in WO 0275312 (Gyros AB) applicant has found that samples many times may contain disturbing substances that are capable of negatively affecting results related to desired reactions between an immobilized reactant and a solute. These substances may be low molecular compounds, aggregates and/or particulate material. For biologically derived samples particulate material may be cell debris and the like, lipids etc. The problem encountered may be linked to the type of solute that is to react with the immobilized reactant, thus for instance membrane associated biological molecules typically are accompanied by relatively large amounts of particulate material, solutes and the like that are difficult to handle in a microfluidic device, for instance in cell lysate preparations and other samples deriving from cells, tissue and body fluids.

One of the present inventors has realized that these problems many times can be wholly or partially overcome by designing the porous bed to have an upstream part that is not exposing the immobilized reactant to a through-passing liquid containing the solut (dummy or blank part in relation to solute (S)). This inventor has also realized that by properly selecting the solid phase material in the upper part it will be possible to delay disturbing particulate material and/or disturbing low molecular weight solutes

GY 0068SE

29

2004-0129

to enter downstream into the microchannel structure where the desired reaction is to take place.

Other kinds of segmented porous beds in microfluidic devices have previously been suggested for other purposes. See US 6,632,655 (Caliper).

The characteristic feature of the 4<sup>th</sup> aspect is thus that the porous bed comprises a downstream part and an upstream part abutting the downstream part, possibly with a porous membrane between the parts securing physical separation of the material of one part from the material of the other part. The immobilized reactant is then primarily exposed in the downstream part.

According to this aspect the solid phase material in both parts may be in wet or in dry state as discussed for the 1<sup>st</sup>, 2<sup>nd</sup> and 3<sup>rd</sup> aspects. The solid phase material may or may not contain a bed-preserving agent of the kind discussed for the same aspects.

This 4<sup>th</sup> aspect also comprises the use as defined for the 3<sup>rd</sup> aspect with the proviso that the microfluidic device provided in step (i) is according to this fourth aspect, and step (ii) is only needed in the case the solid phase material is in dry state.

The solid phase material in the upstream and the downstream part may be of the same or different kind. Thus the downstream part may be a porous monolithic plug and the upstream part a packed bed of particles, or the other way round, or both parts may be porous monoliths or porous beds of packed particles. The solid phase material in the two parts may also differ with respect to one or more of base material, particle size (and particle size distribution), porosity, coatings, hydrophilicity/hydrophobicity, swellability, elasticity, rigidity etc. Typically these features are selected as generally outlined for the 1<sup>st</sup>, 2<sup>nd</sup> and 3<sup>rd</sup> aspects.

The upstream part of the porous bed typically acts as a filter for mechanically preventing particulate material in a sample from penetrating the downstream part in which the intended reaction is to take place.

GY 0068SE

30

2004-0129

2004-01-29

The solid phase material is preferably a size exclusion material because this kind of media with the appropriate size exclusion at least potentially will render it difficult or even prevent a solute having a smaller size than

- a) the solute S that is to react with the immobilized reactant, and/or
- 5 b) other reactants that are needed for desired reactions downstream the upper part of the porous bed

from penetrating the lower part of the porous bed. Preferred size exclusion material or media are liquid chromatography size exclusion material including in particular gel filtration material. In this context "a smaller size" typically refers to a lower molecular

10 weight and/or a smaller hydrodynamic size. Low molecular weight solutes may be found amongst solutes having molecular weights  $\leq 100,000$  dalton, such as  $\leq 50,000$  dalton or  $\leq 10,000$  dalton or  $\leq 7,000$  dalton and are ultimately determined relative to the molecular weight and/or size of the solute(s) that one wants to pass through the upstream part.

15

It is believed that proper size exclusion media are selected amongst this kind of media that have  $K_{av}$ -values  $< 0.5$ , such as  $< 0.4$  or  $< 0.1$ , for solutes that are to pass through the upstream part of the porous bed and used as reactants downstream this part. More particularly suitable size exclusion media should have a  $K_{av}$ -value within the range of

20 0.1-0.95, typically within 0.40-0.95, for those solutes that are to be prevented from reaching the downstream part of the porous bed. For a definition of  $K_{av}$  see L. Hagel in "Protein Purification, Principles, High Resolution, and Applications", J-C Janson and L Rydén (Eds), VCH Publishers Inc. New York, 1989, p. 99.

- 25 Typical size exclusion media comprise particles that may be packed to a porous bed. Size exclusion media may also be in the form of monolithic porous plugs comprising through-passing pores in which convective mass transport can take place and other smaller pores in which primarily mass transport by diffusion takes place. See for instance WO9839094 (Pharmacia Biotech AB).

30

The immobilized reactant is typically selected amongst the same kinds of immobilized reactants as discussed for the 1<sup>st</sup>, 2<sup>nd</sup> and 3<sup>rd</sup> aspects of the invention. Thus the reactant in the most typically embodiments of the invention is an affinity reactant ( $AC_s$ ) that is

GY 0068SE

31

2004-0129

an affinity counterpart (AC<sub>s</sub>) to the solute (S). Other reactants are also selected according to the outlining for these aspects.

The solid phase material in the upstream part may also expose an immobilized reactant which typically binds to a different solute compared to the immobilized reactant in the downstream part. The immobilized reactant, if present, in the upstream part may be selected amongst the same groups as the reactant in the downstream part except that it has essentially no binding to the solute S when attached to the solid phase material.

10

Other embodiments given for the 1<sup>st</sup>, 2<sup>nd</sup> and 3<sup>rd</sup> aspects are typically also applicable to the 4<sup>th</sup> aspect.

#### BEST MODE

The best mode of the 1<sup>st</sup>, 2<sup>nd</sup> and 3<sup>rd</sup> aspects of the invention at the filing of this application is given in the experimental part and encompasses the solid phase materials shown, trehalose as bed-preserving agent, potassium phosphate as additional additive (buffer), and a microfluidic device with the microchannel structures given in figure 1.

20

The best mode of the 4<sup>th</sup> aspect is given in the experimental part.

### EXPERIMENTAL PART

#### FIGURES

Figure 1 gives a subgroup of microchannel structures of the microfluidic device utilized in the experimental part.

Figures 2a and b show a swellable solid phase material in particle form (Superdex Peptide, Amersham Biosciences, Uppsala, Sweden) placed in a reaction microcavity (104a-l). In figure 2a the particles have been lyophilized and lumped together scattered randomly in the reaction microcavity. No packed bed is at hand. In figure 2b the solid phase material has been reconstituted to well-ordered a porous bed.



GY 0068SE

32

2004-0129

Figure 3 shows monodisperse essentially non-swellable and hydrophilic particles

packed to a porous bed after lyophilisation in a reaction microcavity (104a-h). The bed looked essentially the same after reconstitution (not shown) and therefore no figure has been included.

5 Figures 4a and b show the effect of drying (lyophilization) together with potassium phosphate buffer on the performance of a packed bed of particles to which streptavidin had been immobilized. Fluorescence intensity in radial direction through the bed is given. Storage for one month at +4°C. The effect is measured in a fluorescence myoglobin immunoassay at four different  
10 myoglobin concentrations and compared with the performance of a bed of the same material that has not been dried (lyophilized) (slurry). The myoglobin concentrations were 4.56 nM (1), 22.8 mM (2), 91.2 (3) and 273.6 (4). Figure 4a lyophilization and storage together with potassium phosphate. Figure 4b without lyophilization.

15 Figures 5a-d show the effect of three different drying procedures with a bed-preserving agent (sugar variant, trehalose) on the performance of a packed bed of particles to which streptavidin is covalently coupled. Storage and measurement is the same as for figures 4a-b. Figure 5a is without drying (slurry), figure 5b spin-drying, figure 5c is vacuum-dried, and figure 5d  
20 lyophilization.

Figure 6. Integrated signals are shown for three antibody pairs with the different porous beds. In each group the left column represents the non-segmented bed. The middle and right column represent alternative (a) and (b), the middle column the alternative (a). The bars represent the total integrated  
25 signals from undiluted stimulated cell lysate prepared in triplicates. The segmented bed with the Superdex™ peptide revealed increased signals for all three antibody combinations.

30 The microfluidic device used for the experiments was circular and of the same dimension as a conventional CD (compact disc). The microfluidic device will be called CD in the experimental part. The CD contained 14 groups of 8 microchannel structures arranged as an annular zone around the center (spin axis) of the disc with a

GY 0068SE

33

2004-0129

common waste channel for each group close to the periphery. A group of 8 microchannel structures is shown in figure 1 and is similar to and function in the same manner as the group of microchannel structures illustrated in figures 1-2 of (WO 0275312, Gyros AB) and the corresponding figures in PCT/SE02/01678 (Gyros AB) and PCT/SE02/01701 (Gyros AB). The dimensions are essentially of the same size as in these earlier patent applications.

Each subset (100) comprises 8 microchannel structures (101a-h), one common inlet arrangement (102) and eight separate inlet arrangements (103a-h), and eight reaction microcavities (104a-h). The common inlet arrangement comprises a) two inlet ports (105a-b) that also will function as outlet port for excess liquid, and b) one volume-metering unit (106a-h) for each microchannel structure (101a-h). The volume-metering units (106a-h) will function as a distribution manifold for the downstream parts of the microchannel structures. Each of the separate inlet arrangements (103a-h) is part of only one microchannel structure and comprises an inlet port (107a-h) and a volume-metering unit (108a-h). Between each volume-metering unit (106a-h, 108a-h) and their downstream parts, respectively, there is a valve function (109a-h, 110a-h), preferably passive. A reaction macrocavity (104a-h) of a microchannel structure (101a-h) is located downstream both the common inlet arrangement (102) and the separate inlet arrangement (103a-h) of a microchannel structure (101a-h). At the outlet end (111a-h) of each reaction microcavity, the depth is lowered from 100  $\mu\text{m}$  to 10  $\mu\text{m}$  in two steps to prevent particles from escaping the reaction microcavity. At the periphery there is a common waste channel (112). Vents (113a-i) together with the valves (109a-h) define the volume of the liquid aliquots to be distributed downstream from each the volume-metering unit (106a-h).

By applying the appropriate volume of aqueous liquid to the inlet port of an inlet arrangement, capillarity will fill the volume-metering unit(s) connected to the inlet port with liquid. By spinning the disc around its center, liquid can be forced to pass the valve between a volume-metering unit and downstream parts.

## EXPERIMENTALS

### Instrumentation

GY 0068SE

34

2004-0129

Hälsö AB, Uppsala

The immunoassay was performed in an automated system. The system (Gyrolab

Workstation, prototype 2 instrument equipped with a Laser Induced Fluorescence (LIF) module, Gyros AB, Uppsala, Sweden) was equipped with a CD-spinner, holder for microtiter plates (MTP) and a robotic arm with a holder for 10 capillaries

- 5 connected to 5 syringe pumps, 2 and 2. Two of the capillaries transferred all the reagents and buffers from a MTP to either of the two common inlet ports (105a-b) in the CD. The other eight capillaries transferred individual samples from a MTP to the separate individual inlet ports (107a-h) in the CD.

- 10 The Gyrolab Workstation is a fully automated robotic system controlled by application-specific software. An application specific method within the software controls the spinning of the CD at the precisely controlled speeds and thereby controls the movement of liquids through the microstructures as the application proceeds. Special software was included in order to reduce background noise.

15

See also WO 02075312 (Gyros AB), PCT/SE02/01678 and US 10/062,258 (Gyros AB), and PCT/SE02/02455 and 10/331,399 (Gyros AB) and also [www.gyros.com](http://www.gyros.com).

#### **Solid phase, immobilization of streptavidin, packing, drying/dehydration and**

#### **20 reconstitution**

The solid phase bead material packed in the microstructures of the microfluidic device could be of either a porous or solid nature. For example polystyrene particles (15 mm, Dynal Biotech, Oslo, Norway) were selected for the solid phase. The beads were modified by passive adsorption of phenyl-dextran (Phe-Dex) to create a hydrophilic

- 25 surface and were subsequently covalently coupled with streptavidin (Immunopure Streptavidin, Pierce, Perbio Science UK Limited, Cheshire, United Kingdom) using CDAP chemistry (Kohn & Wilchek, Biochem. Biophys. Res. Commun. 107 (1982), 878-884). Other particles as Superdex Peptide and Sepharose HP (Amersham Biosciences, Uppsala, Sweden) have also been covalently coupled with streptavidin
- 30 using CDAP chemistry (without phenyl-dextran coating). Streptavidin-biotin is a well-known bioaffinity pair. The polystyrene particles are solid and non-swellable. Superdex Peptide and Sepharose HP are porous for many affinity reactants and swellable in the liquids used.

GY 0068SE  
2004-0129

35

Ink. t. Patent- och reg.verket

2004-01-29

Häro Patent, Kungälv

- After coupling with the streptavidin, a suspension of the particles in potassium phosphate buffer (10mM) without bed-preserving agent or with bed-preserving agent (in this case a sugar additive (10-100 mM)) was distributed in the common
- 5 distribution channel via inlet port (105a-b) and moved through the structure by centrifugal force. The centrifugal force combined with the vents (109a-h,113a-i) divide the suspension in the common inlet arrangement (102) in equal portions, each of which forms a bed of packed particles (column) in each reaction microcavity (104a-h) against the dual depth (111a-h). The approximate volume of the column was
- 10 15 nl. The columns/beds were dried/dehydrated by three various methods:
- Spin-drying: The microfluidic device containing the wet porous beds was spun for one minute at 6000 rpm to remove as much of the fluid as possible before the device was put into a jewel case and sealed in a polymer-coated aluminum bag.
- Vacuum-drying: The microfluidic device containing the wet porous beds was placed
- 15 on trays and put into a vacuum drying oven (Heraeus vacutherm VT6060M). The temperature was set to 25 °C and the pressure was reduced by vacuum to 0.1 millibars. The device was maintained at this pressure and temperature for half an hours, until the product was dried. The pressure was then allowed to reach atmospheric pressure. The device was then placed into a jewel case and sealed in a
- 20 polymer-coated aluminum bag.
- Freeze-drying (lyophilization): The microfluidic device containing the wet porous beds were placed on a tray and put into a -80 °C freezer. (The device could also be placed in an ordinary -20 °C freezer for an hour.) After a few minutes all columns in the device were freezed and the trays where transferred to a freeze-dryer apparatus (Heto,
- 25 LyoPro 3000) in which the condenser temperature was set to -57 °C. The pressure was reduced (by vacuum) to 0.1-0.06 millibars. The device was maintained at this pressure and temperature until all of the ice had sublimed (about 12 hours or over night). The pressure was then allowed to reach atmospheric pressure during 2 minutes before the chamber was opened and the lyophilized product was provided in the
- 30 device. The device was put into a jewel case and sealed in a in a polymer-coated aluminum bag.

GY 0068SE

36

2004-0129

The devices were stored for one month at +4°C after which the dry columns were rewetted/reconstituted once with 15 mM phosphate buffer (PBS), pH 7,4 containing 0,15 M NaCl, 0,02% NaN<sub>3</sub> and 0,01% Tween 20 via the common distribution channel and spinning at the appropriate rate. Every addition of solution delivers 200 nl liquid to the individual column (104a-h). Finally the function of the reconstituted beds was tested in the immunoassay given below at four different analyte (myoglobin) concentrations and compared with the corresponding beds that had not been dried/dehydrated. The results are presented in figures 4-5 and show that it is imperative to include a bed-preserving agent in order to reconstitute the dry/dehydrated solid phase material to an efficient wet porous bed.

### Immunoassay

The catching antibody in our myoglobin assay, the monoclonal antimyoglobin 8E11.1 (LabAS, Tartu, Estonia) was biotinylated using Sulfo-NHS-LC-biotin (Pierce, prod # 21335, Perbio Science UK Limited, Cheshire, United Kingdom). The protein concentration of the monoclonal antimyoglobin 8E11.1 was 1-10 mg/ml and it was incubated in room temperature for 1 h with 3× molar excess of the biotinylation reagent in 15 mM PBS with 0,15 M NaCl before it was gel filtrated through either a NAP-5 column (Amersham Biosciences, Uppsala, Sweden) or a Protein Desalting Spin Column (Pierce, # 89849-P, Perbio Science UK Limited, Cheshire, United Kingdom).

To load the streptavidin immobilized particles with the biotinylated antibody, a solution at a 0,2-2 mg/ml concentration (depending of how much streptavidin it is in the packed column) of antibody was distributed in the common distribution channel via inlet port (105a-b) and moved through the structure by centrifugal force. The flow rate through the columns was controlled by the spin velocity (spin flow 1). After the capturing antibody was attached to the columns they were washed once by addition of PBS (with 0,01% Tween 20) to the common distribution channel (inlet ports 105a or b) followed by a spin step.

To demonstrate the myoglobin assay in Gyrolab Workstation a 6-point standard curve was created. The myoglobin samples (diluted in PBS with 1% BSA) with

GY 0068SE

37

2004-0129

concentrations in the range of 0-274 nM where distributed to the individual inlet ports

(107a-h) by the capillaries. The sample volume 200 nl was defined into the volume-

metering unit (108a-h), during the first two steps in the spin flow method. To reach

favourable kinetic condition under the capturing step (for myoglobin to bind to

5 8E11.1) the flow rate of the sample should not exceed 1 nl/sec. The sample flow rate

was controlled by spin flow 2. After sample capturing the columns was washed twice

by addition PBS (with 0,01% Tween 20) to the common distribution channel (inlet

port 105a or b) followed by a spin step. Detecting antibodies (monoclonal

antimyoglobin 2F9.1 (LabAs, Tartu, Estonia)) in excess were applied next via the

10 common distribution channel (inlet port 105a or b) and a similar slow flow rate (spin

flow 3) was used. The detecting antibodies were labeled with a fluorophore Alexa 633

(Molecular Probes, Eugene, USA). Excess of labeled antibody was washed away by 4

additions of PBS (with 0,01% Tween 20) to the common distribution channel (inlet

port 105a or b) followed by a spin step.

15

The complete assay was analyzed in the Laser Induced Fluorescence (LIF) detector

module. See more WO 02075312 (Gyros AB), PCT/SE02/01678 and US 10/062,258

(Gyros AB), and PCT/SE02/02455 and 10/331,399 (Gyros AB).

20 An overview of the run method performed in the system is presented in Table 1.

Table1

METHOD	SPIN PROFILE
Rewetting of bead columns	
Spin 1	2500 rpm 5s, 6000 rpm 10s
Wash of beads	
Spin 2	1200 rpm 2s, 2500 rpm 0,5s, 4000 rpm 10s, 6500 rpm 16s
Transfer of biotinylated antibody	
Spin flow 1	1200 rpm 2s, 2500 rpm 0,5s, from 1200-1500 rpm 45s, 2000 rpm 35s, 3000 rpm

GY 0068SE  
2004-0129

38

Handwritten: 10 min

	30s, 4000 rpm 10s, 5000 rpm 5s, 6000 rpm 10s
Wash of beads and CD-structure 1	
Spin 3	1200 rpm 2s, 2500 rpm 1s, 4000 rpm 15s, 6000 rpm 18s
Transfer of myoglobin samples	
Spin flow 2	1000 rpm 5s, 2500 rpm 0,5s, from 1200-1500 rpm 90s, 2000 rpm 70s, 3000 rpm 60s, 4000 rpm 20s, 5000 rpm 10s
Myoglobin wash 1	
Spin 4	1200 rpm 2s, 2500 rpm 0,5s, 4000 rpm 10s, 6000 rpm 16s
Myoglobin wash 2	
Spin 5	1200 rpm 2s, 2500 rpm 0,5s, 4000 rpm 10s, 6000 rpm 16s
Transfer of conjugate	
Spin flow 3	1200 rpm 2s, 2500 rpm 0,5s, from 1200-1500 rpm 90s, 2000 rpm 70s, 3000 rpm 60s, 4000 rpm 20s, 5000 rpm 10s
Conjugate wash 1	
Spin 6	1200 rpm 2s, 2500 rpm 0,5s, 4000 rpm 10s, 6000 rpm 16s
Conjugate wash 2	
Spin 7	1200 rpm 2s, 2500 rpm 0,5s, 4000 rpm 10s, 6000 rpm 16s
Conjugate wash 3	
Spin 8	1200 rpm 2s, 2500 rpm 0,5s, 4000 rpm 10s, 6000 rpm 16s
Conjugate wash 4	
Spin 9	1200 rpm 2s, 2500 rpm 0,5s, 4000 rpm 10s, 6000 rpm 16s
Detection	

GY 0068SE  
2004-0129

39

Drying and reconstitution

#### COMPARISON BETWEEN SEGMENTED POROUS BEDS AND NON-SEGMENTED POROUS

##### 5 BEDS

This example is part of an investigation in which PDGF  $\beta$ -receptor in cell lysates from porcine aorta endothelial (PAE) cells stably expressing the membrane bound PDGF  $\beta$ -receptor and stimulated with +/- ligand PDGF-BB was assayed. The assaying method was a sandwich immunoassay utilizing one antibody raised against the target protein and another antibody raised against one regulatory phosphorylated aminoacid or site. The sandwich immunoassay utilized the same streptavidin-phenyldextran coated solid phase as for assaying myoglobin above. The capture antibody was biotinylated by the same method as the capture anti-myoglobin antibody above. The detection antibody was labelled with Alexa 647 detection reagent by the same methodology as the detection anti-myoglobin antibody above.

The assay was performed in the same kind of microchannel structure/microfluidic device/instrument as the myoglobin assay.

##### 20 Cell culture

The cell lysate preparations derived from porcine aorta endothelial (PAE) cells stably expressing the PDGF  $\beta$ -receptor. The PAE cells were transfected with PDGF  $\beta$ -receptor and one of the cell cultures were also G-418 selected [Claesson-Welsh, L. et al. *cDNA cloning and expression of a human platelet-derived growth factor receptor specific for B-chain containing PDGF molecules*. Mol. Cell. Biol. 8 (1988) 3476-3486]. PAE cells were grown in Ham's F-12 medium supplemented with 10% fetal calf serum, 100  $\mu$ g/ml streptomycin and the amino acid glutamine. A nearly confluent monolayer of cells were starved overnight in Ham's F-12 supplemented with 0.1 mg/ml bovine serum albumin (BSA) and +/- stimulated with 100 ng/ml PDGF-BB for 60 minutes on a shake plater. Unstimulated cells are used as a control since they have no activated PDGF  $\beta$ -receptors, only unphosphorylated PDGF  $\beta$ -receptors. The receptors are activated and saturated with high concentration of ligand inhibiting internalisation followed by degradation during the stimulation. After the stimulation,



2004-01-29

GY 0068SE

40

Huvudlaborant, Huddinge

2004-0129

- cells were washed two times in ice-cold PBS buffer and scraped off with a "rubber police men" in 1 ml PBS. The cell suspension were saved and lysed in 200 µl ice-cold lysis buffer (20 mM Tris-HCl pH 7.5, 150 mM NaCl, 10 mM EDTA, 0.5% Triton X-100, 0.5% Deoxycholate, 0.5 mM  $\text{Na}_3\text{VO}_4$  and 1% Trasylol from Bayer) for 15 min on ice. The lysates were centrifuged at 13000 rpm for 15 min at 4°C and the supernatant were saved in aliquots and stored at -20°C. The cell lysate preparation was done twice and the first time the cells were grown in 75 cm<sup>2</sup> culture dishes and the second time they were grown in 175 cm<sup>2</sup> culture flasks in order to make more concentrated lysates. The quantitation of total protein was done according to BCA Protein Assay Kit Microplate procedure from PIERCE Biotechnology (Boule Nordig AB, Huddinge, S.) and this Protein assay is based on bicinchoninic acid (BCA).

#### *PDGF $\beta$ -receptor antibodies*

- The rabbit polyclonal antibody 958 directed against a recombinant protein corresponding to amino acids 958-1106 of the carboxy terminus of human PDGF  $\beta$ -receptor, the goat polyclonal antibody P-20, raised against a peptide of the carboxy terminal of human PDGF  $\beta$ -receptor, and the mouse monoclonal PY99 were all from Santa Cruz Biotechnologies (Santa Cruz, CA). The PDGF  $\beta$ -receptor antibodies P-20 and 958 are recommended for the detection of PDGF receptor type  $\beta$  of human and, to a lesser extent, mouse and rat origin by western blotting, immunoprecipitation and immunohistochemistry and should not be cross reactive with PDGF receptor type  $\alpha$ . The antibodies have been used extensively in immunoprecipitation and Western Blot experiments with the same cell culture, one example described in reference [Pietras K., et al. Inhibition of PDGF Receptor Signaling in Tumor Stroma Enhances Antitumor Effect of Chemotherapy. Cancer Research 62 (2002) 5476-548].

#### *Sandwich-based immunoassay methods*

- In the cell lysate assay, wash buffers and antibodies were distributed through the common distribution channel and cell lysate preparations were distributed through the individual inlet. Every batch run included standards in triplicates and blank samples; The cell lysate assay included a small dilution serie (+/- PDGF-BB) and several

GY 0068SE

41

H. Franzen

2004-0129

blanks with lysis buffer. All steps in the assay were automatically run in the Gyrolab Workstation.

In the cell lysate assay several different combinations of the three antibodies were tested in order to find out what antibody pair that gives the highest degree of specific binding, 958/PY99, 958/P-20, P-20/P-20, P-20/958 and P-20/PY99 (capturing/detecting).

By titration of the detection antibody it was determined that the concentration of the detection antibody should be 400 nM.

The  $\beta$ -PAE cell lysate with +/- PDGF-BB stimulation was diluted in lysis buffer (2 x, 4 x, 8 x) and undiluted cell lysate was also included as a standard point.

**15 Immobilization of capture antibody:** The porous beds were washed twice with wash buffer PBS-T (0.015 M Na-PO<sub>4</sub> pH 7.4, 0.15 M NaCl, 0.01% NaN<sub>3</sub>, 0.01% Tween-20) in order to recondition the streptavidin-coated particles followed by a short spin. The second step was addition of biotinylated capture antibody at a concentration of 667 nM followed by a spin and through the streptavidin-biotin interaction the capture antibody was bound to the solid phase. The capture antibody was diluted in wash buffer described above. After the immobilisation of capture antibody, two wash steps were performed with wash buffer and the same short spin as the previous wash steps.

**Basic assay protocol:** The cell lysate samples were added to the individual inlet in the microstructures. The subsequent spin made volume definition possible and 200 nl aliquots of sample were run into the porous beds, allowing capture antibody to interact with PDGF  $\beta$ -receptor molecules (analyte). Two wash steps were performed and the latter followed by a very short spin to ensure that the beds were filled with liquid during the fluorescence detection. The background fluorescence detection included three detection steps with different sensitivity set on the LIF detector (laser induced fluorescence detector), 1%, 5% and 25%. Excess buffer was washed away by a short spin before the addition of the labelled detection antibody. The detection antibody was allowed to bind to the analyte during the following spin step and the

GY 0068SE

42

2004-0129

sandwich immunoassay was formed with capture antibody on solid phase, analyte attached to capture antibody and detection antibody bound to analyte. Six wash steps were included, two times with normal wash buffer and four times with wash buffer including isopropanol 20%, to remove all unreacted detection antibody.

5

In the beginning cell lysate runs were mainly performed according to the basic assay protocol with the capture anti body being distributed all over the porous bed.

Modifications were tested because of difficulties to establish a specific interaction between the PDGF $\beta$ -receptor and the antibodies. First of all, the analyte and the

10 detection antibody spin program were extended and the linear flow over the bed reduced to enable the PDGF  $\beta$ -receptor in the cell lysate to attach to the capture antibody. After analyte addition three extra wash steps were included with PBS buffer without Tween-20 and the second and the fourth wash step were followed by a pulsed spin program, allowing the solution to move through the beds by simple diffusion.

15 The final wash steps after detection antibody was the same with the exception that isopropanol was excluded in the wash buffer.

Due to a lot of uncontrolled non-specific interactions in the cell lysate assay a segmented porous bed containing an upstream part devoid of capture anti-ana

antibody and a downstream part exposing anti-analyte antibody was loaded in reaction microcavities of the microstructures. The gel filtration particle Superdex™ peptide (Amersham Biosciences, Uppsala, S.) was loaded in a 5 x dilution slurry onto the existing polystyrene phenyldextran particle beds. Superdex™ peptide is used for high-resolution gel filtration of peptides and other small biomolecules of 100-7000 molecular weight.

## RESULTS

From pre-experiments three antibody pairs were selected P-20/958, P-20/PY99 and 958/PY99.

30

**Non-segmented porous bed.** In general the cell lysate runs revealed high CV values due to the signal distribution where a lot of variation between the triplicates was seen. In some cases a small difference in signal could be seen between undiluted cell lysate

GY 0068SE

43

2004-0129

and blank signals but mostly significant signals were hard to distinguish from background signals. The enrichment in the beds was mostly irregular and a general bed pattern could not be seen, in some cases the signal had a tendency to progress down the porous bed.

5

**Segmented porous bed.** Two types of segmented porous beds were tested:

- a) a bed of polystyrene particles (essentially non-porous) coated with phenyldextran on top of a bed of polystyrene particles coated with phenyldextran to which streptavidin has been immobilized, and
- 10 b) a bed of Superdex™ peptide on top of a bed of polystyrene particles coated with phenyldextran to which streptavidin has been immobilized.

In particular for the Superdex™ peptide segmented bed showed an improvement in signals for the three antibody pairs compared to the non-segmented bed. See in figure 6. Differences between cell lysate and blank responses could also be discerned.

15

Certain innovative aspects of the invention are defined in more detail in the appending claims. Although the present invention and its advantages have been described in detail, it should be understood that various changes, substitutions and alterations can be made herein without departing from the spirit and scope of the invention as defined

- 20 by the appended claims. Moreover, the scope of the present application is not intended to be limited to the particular embodiments of the process, machine, manufacture, composition of matter, means, methods and steps described in the specification. As one of ordinary skill in the art will readily appreciate from the disclosure of the present invention, processes, machines, manufacture, compositions
- 25 of matter, means, methods, or steps, presently existing or later to be developed that perform substantially the same function or achieve substantially the same result as the corresponding embodiments described herein may be utilized according to the present invention. Accordingly, the appended claims are intended to include within their scope such processes, machines, manufacture, compositions of matter, means,
- 30 methods, or steps.

GY 0068SE  
2004-0129

44

2004-01-29

Inventor: Fran-Åkesson

## CLAIMS

1. A microfluidic device that comprises one, two or more microchannel structures,  
each of which comprises a reaction microcavity retaining a solid phase material in  
the form of a wet porous bed, a reactant being exposed in immobilized form on  
5 the solid phase material and capable of interacting with a solute (S) in a liquid  
passing through the bed, characterized in that
  - a) the porous bed comprises a downstream part and an upstream part abutting  
the downstream part, possibly with a porous membrane between the parts  
securing physical separation of the material of one part from the material of  
10 the other part, and
  - b) the immobilized reactant is primarily exposed in the downstream part.
2. The microfluidic device according to claim 1, characterized in that the porous  
bed is a packed bed of particles in at least one of the upstream and the downstream  
15 part and a porous monolithic plug in the other part, if any.
3. The microfluidic device according to any of claims 1-2, characterized in that the  
solid phase material in the upstream part comprises a size exclusion material  
permitting the solute s to pass through essentially unhindered compared to one or  
20 more solutes that negatively affects desired reactions downstream the upstream  
part, said size exclusion material preferably being a liquid chromatographic size  
exclusion material such as a gel filtration material
4. A microfluidic device comprising one, two or more microchannel structures, each  
25 of which comprises a reaction microcavity intended for retaining a solid phase  
material in the form of a wet porous bed, characterized in that each of said one,  
two or more microchannel structures comprises the solid phase material in a dry  
state that also comprises a bed-preserving agent comprising one or more  
compounds having bed-preserving activity.  
30
5. The microfluidic device according of claims 4, characterized in that at least one  
of said one or more compounds a) exhibit a hydrophilic group that may or may not  
be non-ionic, and b) are water-soluble.

GY 0068SE  
2004-0129

45

6. The microfluidic device according to any of claims 4-5, characterized in that at least one of said one or more compounds is a polyol.
- 5 7. The microfluidic device according to any of claims 4-6, characterized in that at least one of said one or more compounds exhibits carbohydrate structure, such as polysaccharide structure or oligosaccharide structure.
8. The microfluidic device according to any of claims 4-7, characterized in that at least one of said one or more compounds is a disaccharide, preferably trehalose.
- 10 9. The microfluidic device according to any of claims 4-8, characterized in that at least one of said one or more compounds can be in a glassy state in at least a part of the interval +15-35°C.
- 15 10. The microfluidic device of any of claims 4-9, characterized in that at least one of said compounds is a microcavity adherence agent.

GY 0068SE  
2004-0129

46

## ABSTRACT

Int. t. Patent- och register

1998-01-01

Hälsö, S. 1000

A microfluidic device that comprises one, two or more microchannel structures, each of which comprises a reaction microcavity retaining a solid phase material in the form of a wet porous bed, a reactant being exposed in immobilized form on the solid phase material and capable of interacting with a solute (S) in a liquid passing through the bed. The device is characterized in that

- a) the porous bed comprises a downstream part and an upstream part abutting the downstream part, possibly with a porous membrane between the parts securing physical separation of the material of one part from the material of the other part, and
- b) the immobilized reactant is primarily exposed in the downstream part.

A microfluidic device comprising one, two or more microchannel structures, each of which comprises a reaction microcavity intended for retaining a solid phase material in the form of a wet porous bed. Each of said one, two or more microchannel structures comprises the solid phase material in a dry state together with a bed-preserving agent comprising one or more compounds having bed-preserving activity.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123





Ek t. Patent- och registerverket

07:1 -01- 2 9

Per-Olofsson Kasson

2/2  
2/6

Figure 2a





Figure 5b.



29-01-2004 11:39

FRAN-GYROS AB

+4618566350

+46 18 566350

T-025 P.084/059 F-406


Ink. t. Patent- och reg.verket

2004-01-29

Upplyst av Kasseran

3/6 3/2

Figure 3



01000014



lek. t. Patient- och produktregister

S 11-01-2 9

Hälsö 11-01-2 9

5/6 5/2

Figure 5a





Figure 5b



Link L. Rönt- och röntverket

11-01-2004

Rönt- och röntverket

6/6 6/2

Figure 5c





Figure 5d



7/7




Figure 6

04001014